

DF2-3

DF2-3系列焊接机专用二位二通电磁阀

DF2-3 Series Two-position Two-way Solenoid Valve for Welding Machinery



产品概述 / Product overview

产品册将DF2-3-A、DF2-3-B和DF2-3-C列在“焊接机专用电磁阀”页面，三款均为二位二通结构，工作压力均为0–10 kgf/cm²。

The catalog lists DF2-3-A, DF2-3-B and DF2-3-C on its solenoid-valve page for welding machinery. All three use a two-position two-way construction and have a listed working pressure of 0–10 kgf/cm².

产品特点 / Product features

- 二位二通结构。
- 包含DF2-3-A、DF2-3-B和DF2-3-C三种型号。
- 接管口径包含1/4英寸和1/8英寸。
- 工作温度为-5 ~ 80°C。

Two-position two-way construction.

Includes DF2-3-A, DF2-3-B and DF2-3-C models.

Port sizes include 1/4 inch and 1/8 inch.

Operating temperature is -5 to 80°C.

型号参数 / Model parameters

型号 Model	接管口径 (英寸) Port (inch)	流量孔径 (mm) Orifice (mm)	工作压力 (kgf/cm ²) Working pressure (kgf/cm ²)	Cv值 Cv	工作温度 (°C) Operating temperature (°C)	L (mm) L (mm)	W (mm) W (mm)	H (mm) H (mm)	重量 (kg) Weight (kg)
DF2-3-A	1/4	4	0-10	0.4	-5-80	40	35	62	0.32
DF2-3-B	1/8	3	0-10	0.3	-5-80	32	28	56	0.23
DF2-3-C	1/8	3	0-10	0.3	-5-80	38	31	62	0.24

应用场景 / Applications

用于焊接机械。

For welding machinery.

选型提示 / Selection note

请在询价时提供型号、口径、接口、材质、介质、压力、温度、控制方式和数量；所有供货信息按单确认。

For RFQ, provide model, size, connection, material, media, pressure, temperature, control mode and quantity. Availability is confirmed per order.

资料来源 / Source: AEK 产品技术资料 / AEK technical source material · 2024 catalog; facts below were checked against rendered source pages. · PDF pages 4