

JKH

JKH系列插入式管接头（黄铜）

JKH Series Brass Push-in Tube Fitting



产品概述 / Product overview

JKH系列为采用O形圈密封的黄铜插入式管接头，适用于硬管、半硬尼龙管和塑料管。产品册标注最高工作压力为1.0 MPa，并说明快速插入、拔出及终端接头转向方法。

The JKH series is a brass push-in fitting sealed with an O-ring for hard tubing, semi-hard nylon tubing and plastic tubing. The catalog states a maximum working pressure of 1.0 MPa and describes quick insertion, removal and terminal-fitting orientation.

产品特点 / Product features

- 采用O形圈密封。
- 适用于硬管、半硬尼龙管和塑料管。
- 支持快速插入和拔出，最高工作压力为1.0 MPa。
- 终端接头可转动本体以调整管路方向。

O-ring sealing.

Suitable for hard tubing, semi-hard nylon tubing and plastic tubing.

Supports quick insertion and removal; maximum working pressure is 1.0 MPa.

The body of a terminal fitting can be rotated to adjust the tube direction.

JKH-Z直通终端接头代表型号 / Representative JKH-Z straight terminal fittings

型号 Model	管外径 (mm) Tube OD (mm)	管外径 (英寸) Tube OD (inch)	螺纹规格 Thread options	L (mm) L (mm)	L1 (mm) L1 (mm)
JKH-Z2.5	4	1/8	M6×1	23	5
JKH-Z4	6	1/4	M8×1	27.5	6
JKH-Z6	8	5/16	M10×1; NPT1/8; G1/8; ZG1/8	28	7
JKH-Z8	10	3/8	M12×1.25; NPT1/4; G1/4; ZG1/4	30.5	9
JKH-Z10	12	1/2	M16×1.5; NPT3/8; G3/8; ZG3/8	32	10

应用场景 / Applications

用于硬管、半硬尼龙管和塑料管连接。

For connecting hard tubing, semi-hard nylon tubing and plastic tubing.

选型提示 / Selection note

请在询价时提供型号、口径、接口、材质、介质、压力、温度、控制方式和数量；所有供货信息按单确认。

For RFQ, provide model, size, connection, material, media, pressure, temperature, control mode and quantity. Availability is confirmed per order.

资料来源 / Source: AEK 产品技术资料 / AEK technical source material · 2016–2017 catalog; facts below were checked against rendered source pages.
· PDF pages 144, 146