

JKY

JKY系列卡套式管接头（黄铜）

JKY Series Brass Compression Tube Fitting



产品概述 / Product overview

JKY系列为适用于有色金属管和硬尼龙管的黄铜卡套式管接头。产品册标注最高工作压力为1.0 MPa，并给出切管、去毛刺、插管和紧固步骤。

The JKY series is a brass compression fitting for non-ferrous-metal tubing and hard nylon tubing. The catalog states a maximum working pressure of 1.0 MPa and gives tube-cutting, deburring, insertion and tightening steps.

产品特点 / Product features

- 采用卡套式连接结构。
- 适用于有色金属管和硬尼龙管。
- 最高工作压力为1.0 MPa。
- 安装时将管端切齐并去除毛刺，插到底后按产品册步骤紧固。

Compression connection construction.

Suitable for non-ferrous-metal tubing and hard nylon tubing.

Maximum working pressure is 1.0 MPa.

For installation, square-cut and deburr the tube, insert it fully, then tighten it as described in the catalog.

JKY-Z直通终端接头代表型号 / Representative JKY-Z straight terminal fittings

型号 Model	管外径 (mm) Tube OD (mm)	管外径 (英寸) Tube OD (inch)	螺纹规格 Thread options	L (mm) L (mm)	L1 (mm) L1 (mm)
JKY-Z2.5	4	1/8	M6×1	27.5	5
JKY-Z4	6	1/4	M8×1	30.5	6
JKY-Z6	8	5/16	M10×1; NPT1/8; G1/8; ZG1/8	33.5	7
JKY-Z8	10	3/8	M12×1.25; NPT1/4; G1/4; ZG1/4	36	9
JKY-Z10	12	1/2	M16×1.5; NPT3/8; G3/8; ZG3/8	39.5	10
JKY-Z15	18	5/8	M20×1.5; NPT1/2; G1/2; ZG1/2	46	11
JKY-Z20	22	3/4	M27×2; NPT3/4; G3/4; ZG3/4	54	14
JKY-Z25	28	1	M33×2; NPT1; G1; ZG1	61.5	16

应用场景 / Applications

用于有色金属管和硬尼龙管连接。

For connecting non-ferrous-metal tubing and hard nylon tubing.

选型提示 / Selection note

请在询价时提供型号、口径、接口、材质、介质、压力、温度、控制方式和数量；所有供货信息按单确认。

For RFQ, provide model, size, connection, material, media, pressure, temperature, control mode and quantity. Availability is confirmed per order.

资料来源 / Source: AEK 产品技术资料 / AEK technical source material · 2016–2017 catalog; facts below were checked against rendered source pages.
· PDF pages 140, 142