

JZFAS

JZFAS 塑料头气动螺纹角座阀

JZFAS Pneumatic Threaded Angle-seat Valve



产品概述 / Product overview

JZFAS 为塑料执行头气动螺纹角座阀，适用于中性气体或空气控制。系列覆盖 DN10–DN100，提供 CF8 或 CF8M 阀体、PTFE 阀座及 BSPT 螺纹，并可选 BSP 或 NPT。

JZFAS is a pneumatic threaded angle-seat valve with a polymer actuator head for neutral-gas or air control. The series covers DN10–DN100 with CF8 or CF8M bodies, PTFE seats and BSPT threads; BSP and NPT are optional.

产品特点 / Product features

- 螺纹接口结构，常规采用 BSPT，并可按需求选择 BSP 或 NPT。
- 阀体可选 CF8 或 CF8M，阀杆可选 304 或 316L，阀座为 PTFE。
- 气源压力范围为 0.3–0.8 MPa，公称压力为 1.6 MPa。

The threaded connection is BSPT as standard, with BSP or NPT available on request.

Body material is CF8 or CF8M, stem material is 304 or 316L, and the seat is PTFE.

Air-supply pressure is 0.3–0.8 MPa and nominal pressure is 1.6 MPa.

技术参数 / Technical parameters

项目 Item	参数 Value
介质温度 Medium temperature	-20~180°C
环境温度 Ambient temperature	-20~60°C
公称压力 Nominal pressure	1.6 MPa
控制介质 Control medium	中性气体、空气 Neutral gas, air
气源压力 Air pressure	0.3~0.8 MPa
规格 Size	DN10~DN100
阀体材质 Body material	CF8 / CF8M
阀座材质 Seat material	PTFE
阀杆材质 Stem material	304 / 316L
密封材质 Seal material	NBR
标准螺纹 Standard thread	BSPT
可选螺纹 Optional thread	BSP / NPT

选型提示 / Selection note

请在询价时提供型号、口径、接口、材质、介质、压力、温度、控制方式和数量；所有供货信息按单确认。

For RFQ, provide model, size, connection, material, media, pressure, temperature, control mode and quantity. Availability is confirmed per order.

资料来源 / Source: 爱儿康角座球阀阀样册(1).pdf · 2023 · PDF pages 10