

KH

KH系列插入式管接头 (黄铜)

KH Series Brass Push-in Tube Fitting



产品概述 / Product overview

KH系列为采用O形圈密封的黄铜插入式管接头，适用于硬管、半硬尼龙管和塑料管。产品册标注最高工作压力为1.0 MPa，并列出了直通接头与BSP直通终端接头尺寸。

The KH series is a brass push-in fitting sealed with an O-ring for hard tubing, semi-hard nylon tubing and plastic tubing. The catalog states a maximum working pressure of 1.0 MPa and lists dimensions for straight fittings and BSP straight terminal fittings.

产品特点 / Product features

- 采用O形圈密封。
- 适用于硬管、半硬尼龙管和塑料管。
- 支持快速插入和拔出。
- 最高工作压力为1.0 MPa。

O-ring sealing.

Suitable for hard tubing, semi-hard nylon tubing and plastic tubing.

Supports quick insertion and removal.

Maximum working pressure is 1.0 MPa.

KH直通接头型号 / KH straight-fitting models

型号 Model	管外径 (mm) Tube OD (mm)	L (mm) L (mm)
KH-4	4	31.5
KH-6	6	35
KH-8	8	38
KH-10	10	43
KH-12	12	41.5

KH英制直通终端接头型号 / KH BSP straight terminal fittings

型号 Model	管外径 (mm) Tube OD (mm)	螺纹 Thread	扳手尺寸 (mm) Wrench size (mm)	L (mm) L (mm)	L1 (mm) L1 (mm)
KH-4 1/8 BSP	4	1/8 BSP	12	18	5.5
KH-6 1/4 BSP	6	1/4 BSP	14	21.5	7
KH-8 3/8 BSP	8	3/8 BSP	19	23.5	8
KH-10 3/8 BSP	10	3/8 BSP	19	25.5	8
KH-12 3/8 BSP	12	3/8 BSP	19	28.5	8

应用场景 / Applications

用于硬管、半硬尼龙管和塑料管连接。

For connecting hard tubing, semi-hard nylon tubing and plastic tubing.

选型提示 / Selection note

请在询价时提供型号、口径、接口、材质、介质、压力、温度、控制方式和数量；所有供货信息按单确认。

For RFQ, provide model, size, connection, material, media, pressure, temperature, control mode and quantity. Availability is confirmed per order.

资料来源 / Source: AEK 产品技术资料 / AEK technical source material · 2016–2017 catalog; facts below were checked against rendered source pages.
· PDF pages 146