

SJZF-40

SJZF-40 旋启式止回阀

SJZF-40 Swing Check Valve



产品概述 / Product overview

SJZF-40 为旋启式止回阀。介质按阀瓣开启方向流动时阀门开启，介质倒流时由出口压力推动阀瓣关闭，用于防止管道介质倒流。

SJZF-40 is a swing check valve. The disc opens for flow in the permitted direction and is pressed closed by outlet pressure during reverse flow to prevent backflow in the pipeline.

产品特点 / Product features

- 由阀体、阀瓣和阀座组成，阀瓣绕销轴旋转。
- 顺向流动开启，倒流时自动关闭。
- 产品册说明其密封可靠、流体阻力小。
- 适用于水或蒸汽管路。

The valve comprises a body, disc and seat, with the disc rotating around a pin.

It opens for forward flow and closes during reverse flow.

The catalog describes reliable sealing and low flow resistance.

It is intended for water or steam pipelines.

工作参数 / Operating data

项目 Item	参数 Value
系列公称通径 Series nominal sizes	15-40 mm
公称压力 Nominal pressure	4.0 MPa
工作温度 Operating temperature	≤200°C
适用介质 Media	蒸汽、水 Steam, water

产品册型号与尺寸 / Catalog models and dimensions

型号 Model	公称通径 Nominal size	L	D	D1	D2	DN
SJZF-40	DN40	180	145	110	85	40
XSZF-40	DN25	160	115	85	65	25
XSZF-40	DN40	180	145	110	85	40

应用场景 / Applications

用于工作温度不高于 200°C 的水或蒸汽管路，防止介质倒流。

For water or steam pipelines at operating temperatures up to 200°C to prevent reverse flow.

选型提示 / Selection note

请在询价时提供型号、口径、接口、材质、介质、压力、温度、控制方式和数量；所有供货信息按单确认。

For RFQ, provide model, size, connection, material, media, pressure, temperature, control mode and quantity. Availability is confirmed per order.

资料来源 / Source: 新硫化机样册.pdf · The source PDF metadata dates the catalog to 2024. All products are RFQ-only; configuration, supply and lead time must be confirmed for each inquiry. · PDF pages 11