

VX2120/2220/2320

VX2120/2220/2320系列电磁阀

VX2120/2220/2320 Series Solenoid Valve



产品概述 / Product overview

VX系列包含二位二通常闭式、二位二通常开式和二位三通电磁阀。产品册型号表覆盖1/8、1/4、3/8和1/2英寸接口，并列示空气、水、油、瓦斯和蒸汽介质。

The VX series includes normally closed two-position two-way, normally open two-position two-way, and two-position three-way solenoid valves. The catalog table covers 1/8-, 1/4-, 3/8- and 1/2-inch ports and lists air, water, oil, gas and steam as media.

产品特点 / Product features

- VX2120为二位二通常闭式。
- VX2220为二位二通常开式。
- VX2320为二位三通电磁阀。
- 产品册列示介质为空气、水、油、瓦斯和蒸汽，工作温度为-5 ~ 80°C。

VX2120 is a normally closed two-position two-way valve.

VX2220 is a normally open two-position two-way valve.

VX2320 is a two-position three-way solenoid valve.

The catalog lists air, water, oil, gas and steam, with an operating temperature of -5 to 80°C.

型号参数 / Model parameters

型号 Model	接管口径 (英寸) Port (inch)	流量孔径 (mm) Orifice (mm)	工作压力 (kgf/cm ²) Working pressure (kgf/cm ²)	工作温度 (°C) Operating temperature (°C)	重量 (kg) Weight (kg)
VX2120-08S	1/4	3	0-10	-5-80	0.28
VX2120-06	1/8	3	0-10	-5-80	0.30
VX2120-08	1/4	3	0-10	-5-80	0.28
VX2120-10	3/8	10	0-10	-5-80	0.40
VX2120-15	1/2	10	0-10	-5-80	0.50
VX2220-06	1/8	2	0-7	-5-80	0.28
VX2220-08	1/4	2	0-7	-5-80	0.27
VX2220-06B	1/8	2	0-16	-5-80	0.35
VX2220-08B	1/4	2	0-16	-5-80	0.34
VX2320-06	1/8	2	0-7	-5-80	0.32
VX2320-08	1/4	2	0-7	-5-80	0.30

应用场景 / Applications

用于产品册列示的空气、水、油、瓦斯和蒸汽介质控制；具体工况需按型号表核对压力范围。

Control of air, water, oil, gas and steam media listed in the catalog. The pressure range must be checked against the selected model.

选型提示 / Selection note

请在询价时提供型号、口径、接口、材质、介质、压力、温度、控制方式和数量；所有供货信息按单确认。

For RFQ, provide model, size, connection, material, media, pressure, temperature, control mode and quantity. Availability is confirmed per order.

资料来源 / Source: AEK 产品技术资料 / AEK technical source material · 2024 catalog; facts below were checked against rendered source pages. · PDF pages 4